



SPECIFICATIONS

Electrical
 Current Rating: 5A AC, DC
 Voltage Rating: 250V AC, DC
 Operating Temp.: -25°C ~ +85°C
 Insulation Resistance: 1000MΩ / min.
 Dielectric Withstanding Voltage: 1500V AC/ min.
 Contact Resistance: 10mΩ / max.

Material
 Material: Nylon66, UL94V-2
 Pin : Brass, Tin plated

Poles	Dimension mm (in.)	
	A	B
2	3.96	8.00
3	7.92	12.00
4	11.88	15.90
5	15.84	20.00
6	19.80	24.00
7	23.76	27.90
8	27.72	31.90
9	31.68	35.80
10	35.64	39.90
11	39.60	43.90
12	43.56	47.70

W
2400
02
P
S
N
T
W
0
R

- 1. PRODUCTS: W: Wafer
- 2. SERIES NO.: 2400
- 3. CONTACT NO.: 02-16
- 4. CONTACT TYPE: P: Non Distribution
- 5. FUNCTION: S: Straight, R: Right Angle
- 6. BODY OPTION: Y: W/ Back, N: W/O Back
- 7. CONTACT PLATING: T: Tin
- 8. INSULATOR COLOR: W: White (Standard)
- 9. FILL IT WITH "0"
- 10. R: ROHS

RoHS Compliant

HSM 玄茂科技股份有限公司
 HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准		TOLERANCE 容許公差	PART NAME 品名 3.96mm WAFER STRAIGHT TYPE 1XXXP W/O LOCKING RIBS TIN PLATED WHITE COLOR ROHS
DWG. 製圖		SCALE 比例	
DATE 制表日	UNIT 單位	REV. 版本	PART NO. 料號 W2400-XXPSNTW0R
2020/2/13	M M	A 4	
	PAGE 張數		
	1 OF 1		