

日期/Date
 档案号/ Filing Clerk


技术参数:

- 产品系列: M12 A-code
- 插针数: 4
- 额定电流(40°C): 4A
- 额定电压: 250V
- 额定脉冲电压: 2500V
- 污染等级: 3
- 接触电阻: ≤10mΩ
- 绝缘电阻: ≥100MΩ
- 锁紧方式: 螺纹式M12*1
- 电缆类型: PVC, 黑色RAL9005
- 线规: 0.34mm² (AWG22)
- 防护等级: IP67
- 插拔次数: >100
- 温度范围: -25°C ... +85°C
- 锁紧螺帽: 金属
- 外壳材料: TPU
- 插体材料: PA
- 插针材料: 铜合金
- 插针电镀材料: 金

Technical specification:

- Series: M12 A-Code
- Number of contacts: 4
- Rated current (40°C): 4A
- Rated voltage: 250V
- Rated impulse voltage: 2500V
- Pollution degree: 3
- Contact resistance: ≤10mΩ
- Insulation resistance: ≥100MΩ
- Connector locking system: screw M12*1
- Cable type: PVC, Black RAL 9005
- Wire gauge: 0.34mm² (AWG22)
- Degree of protection: IP67
- Mating cycles: >100
- Temperature range: -25°C ... +85°C
- Material of locking system: Metal
- Material of housing: TPU
- Material of insert: PA
- Material of contact: copper alloy
- Contact plating: Au


插针数 Contacts	料号 Order No.	产品代号 Part Code	电缆长度(L) Cable length	重量 Weight
4	1630045014001	M12-M04A-S-1.5-PVC	1.5m	82g
	1630045014002	M12-M04A-S-5.0-PVC	5mm	245g



剥线长度
 Stripping length of the sheath

例如型号 "M12-M04A-S-L-PVC",
 "L"表示带线长度, 单位m。

Ex: Part code "M12-M04A-S-L-PVC",
 the "L" represents the cable length, unit m.



标记 Mark		处数 Number	变更描述/Description		签名 Signature	日期 Date	表面处理 Finish		图号 Drawing No.	
绘图 Drawn	ZM LIN	15.03.2015	标准化 Stand.	-	-	-	-		-	
审核 Checked	YY LUO	15.03.2015					-		M12-M04A-S-L-PVC	
工艺 Process	-	-	批准 Approved	YY LUO	15.03.2015	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品代号 Part Code
						1:1	V1.0	-	-	产品料号 Part No.
										产品名称 Part Name
										厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD

All Dimensions in mm
 Original Size DIN A 4