



# SPECIFICATION

1. Rated Voltage ..... 1.5V
2. Operating Voltage ..... 1~2V
3. Max. Rated Current ..... 30mA
4. Coil Resistance .....  $16 \pm 2 \Omega$
5. Coil Impedance .....  $40 \Omega$
6. Min. Sound Pressure Level ..... 75dB/10cm
7. Resonant Frequency ..... 2048Hz
8. Case Material ..... PBT
9. Operating Temperature .....  $-20 \sim +70^\circ\text{C}$
10. Store Temperature .....  $-30 \sim +80^\circ\text{C}$
11. Weight ..... 2g

|                            |             |           |      |
|----------------------------|-------------|-----------|------|
| 1.1 PINØ5.5-Ø6.0,Ø4.0-Ø4.5 |             | 08.09.28  |      |
| NO.                        | DESCRIPTION | MEMBER    | DATE |
| FOR DRAWING USE ONLY       |             |           |      |
| NOTED OTHERWISE            |             |           |      |
| XX                         | XX          | XX        | XX   |
| DRAWN                      |             | APPROVALS |      |
| CHECKED                    |             | DATE      |      |
| APPROVED                   |             | DATE      |      |
| 06.03.22                   |             | 06.03.22  |      |

|   |                 |
|---|-----------------|
| Compliance with ROHS  |                 |
| <b>KEPO</b> NINGBO KEPO ELECTRONIC CO.,LTD<br><a href="http://www.chinaacoustic.com">http://www.chinaacoustic.com</a> |                 |
| Magnetic Buzzer   |                 |
| KPM-G1201A1(With KEPO)  |                 |
| UNIT  | DWG NO.         |
| mm  | KP3.840.677.01R |
| SCALE   | NOT TO SCALE    |
| SHEET   | VER             |
| 7   | 1.1             |

